



Key Features

- PTFE Body
- Ceramic Diaphragm
- Teflon Cable
- Full chemical resistant components
- Dual gasket housing and cable seals
- Easy calibration 0- full scale



Specifications

| | | |
|-----------------------|---|--|
| Sensing Technology | - | Piezoresistive |
| Operating Voltage | - | 4.5-15VDC |
| Current Consumption | - | <5mA |
| Operating Temperature | - | -40 > +85C |
| Output Signal | - | 0.5->4.5v, Modbus RS485 Daisy Chain |
| Programmable Units | - | mmH2O, PSI, Bar |
| Accuracy | - | 0.5% full scale |
| Housing | - | PTFE |
| Cable | - | Teflon |
| Diaphragm | - | Ceramic |
| Range | - | 0-5m, 0-7m, 0-11m |
| Tank Connection | - | 2" NPT bushing |

Key Applications

- Aggressive Chemicals
- Fuels- Gasoline, Methanol, Diesel
- Acids- Sulfuric Acid, Hydrochloric Acid
- Liquid Fertilizers
- Fracking Fluids

Contact

- 📍 1125 W. Park One Dr.
Sugar Land, TX 77478
- 📞 972-488-8725
- ✉ Email: sales@levelcon.com
- 🌐 www.levelcon.com